

15" Touch Monitor - PP-6000E



Colors that reflect the user's unique Style & Business Requirements


Features

- 5-Wire Resistive technology
- Combo USB / RS 232 Touch I/F
- Combo internal AC & External DC Adaptor
- MS R Built into the side of 6000E
- VES A 75x75 Mount hole default

Concealed Cable Management Design



I/O Interface



Magnetic Card Reader(Optional)

- * TR1/2/3-I SO7811/12
- * Support Multi-Country MCR code setting
- * Life of Head : 500,000 card swipes

Specification

Parts	Spec. Item	Unit	PP6000E
Lcd Panel	Screen Diagonal	[inch]	15" Active Matrix TFT LCD
	Pixel HxY		1024X768
	Aspect Ratio		4:3 Ratio
	Response Time	[Typ]	8msec
	Support Color		16.2M / 262K colors
	White Luminance	[cd/m2]	250[Typ.]
	Contrast Ratio		700:1(Typ.)
	Surface Treatment		Anti-Glare, Hardness 3H
	Touch Screen	Type	
Interface			USB I/F only / Combo RS232 & USB I/F
OS supported			DOS, WIN, LINUX, IMAX
Video Input	VGA Signal(Input Signal)		Analog RGB
	Scan Frequencies		55-76Hz(V) / 31~80KHz(H)
	Input Video Signal		D-Sub 15 Pin Female Cable
Control	OSD Button		Power / Select / Menu / Up / Down
Power	Type		Combo Internal AC & External DC Adapter
	Input Voltage		Universal AC 100~230 V, 50/60 Hz
	Output Voltage		DC 12V/5V(Inverter/main), 2.5A
	Consumption	[W]	20W
Environment	Temperature	[°C]	Operating : 0~40, Storage : -20~60
	Humidity		Operating : 30~85%, Storage : 5~90%
Weight	Product / Stand	[Grams]	2900 / 1700
Safety & Emi			CE, FCC, RoHS

* Note: All features and specifications are subject to change without notice.
All information subject to mistakes and alteration.

Possibilities & Beyond

rio Retail In
Operation

Ontario, Canada, email: sales@riopos.com
www.riopos.com, www.rio-intl.com