

- Features**
- Data can be display on 20 columns X 2 lines.
 - Display panel is adjustable to provide the best view angle.
 - Provide 2 pole for best position installation.
 - Esc/pos command compatible.
 - International character set is selectable.
 - User-defined characters can be downloaded.
 - User-defined message can be download.
 - Green power function. USB Powered.

Specifications

Model - RPD210

Display

Display method	Vacuum fluorescent display (blue green)
Brightness	700 cd/m2
Number of character	40 characters (20 columns x 2 lines)

Viewing

Character font	5 x 7 Dot Matrix
Character size	3.50mm x 5.00mm
Character type	96 alphanumeric 13 international character sets 1 user define character, 14 code page

Electrical

Power supply	Powered by USB, +5VDC and +9 ~ 35Vdc are optional
Power consumption	2W (Max.)
MTBF	30,000 hours (power on time)

Operations

Operating temperature	0 ~ 45
Operating humidity	10% ~ 90 % RH
Storage temperature	-10 ~ 50
Storage humidity	10% ~ 90 % R H
Module dimensions	146 (W) x 49.2 (H) x 26.4(D) mm
Display dimensions	176(W) x 130(D) 355(H)mm 176(W) x 130(D) 224(H)mm 176(W) x 130(D) 135(H)mm
Connectvity	Data & Power - USB
Module Weight	172g
Display Weight	0.5 Kg

• Note: All features and specifications are subject to change without notice.
All information subject to mistakes and alteration.

