Expertly Engineered with Undeniable Reliability

Compact, convenient, economical printers for retail environments.



Ideal for most environments, its modular casing can switch from a top-load to front-load configuration. Plus, it features simple integration with mobile POS environments, intuitive functionality and advanced connectivity.

Thermal Receipt Printer

- 58mm/82.5mm paper width available
- Dual Interface-options include USB+Serial, USB+Ethernet/ USB+Serial+Bluetooth
- Print Direction: Vertical and Horizontal
- Innovative | AP function,
 Support online update program
- Reliable Cutter, Metallic
 Frame Mechanism



Possibilities & Beyond







RPP 365

Printing Method **Printing Speed** Paper width Printable area

Maximum paper diameter

Paper thickness

Column capacity

Line space Commands Interface type

Character size

Dimension **Gross Weight**

Bar code

2-dimension code

Code Page

Cutter Cutter life

Input buffer **NV Flash**

Print head life

Power adaptor Power source

Cash drawer output Work environment Storage environment Operating system

Direct Thermal 300mm/s 82.5mm

72mm (adjustable by commands)

83 mm

0.06-0.08mm

576 dots/line 512 dots/line

3.75mm (Changeable by commands)

Compatible with ESC/POS

USB+Serial/USB+Lan

ANK, Font A: 12x24 dots 9x17 dots

Font B:

Simplified/traditional Chinese: 24x24 dots

133x126x130mm (DxWxH)

1.115kg

UPC-A/UPC-E/JA(EAN13)/JAN8(EAN8)/CODE39/

ITF/CODABAR/CODE93/CODE128

QR CODE/ PDF417

PC347(Standard Europe), Katakana,

PC850(Multilingual), PC860 (Portuguese), PC863(Canadian-French), PC865(Nordic), WestEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), PC858 Iranll, Latvian, Arabic, PT 151(1251)

Partial

1.5 million cuts

150 KM 64 Kbytes 256 Kbytes

AC110V/220V, 50-60Hz

DC 24V/2.5A DC 24V/1A

Temperature: 0-45C, humidity: 10-80RH% Temperature: -10-60C, humidity: 10-90RH% Win XP/Win Vista/Win 7/Win 8/Win 8.1/

Win10/Linux

[•] Note: All features and specifications are subject to change without notice.